

Performance Data

Unit Size (in.)	Inlet Size (in.)	Air Flow (cfm)	Filter	Static Pressure (in. w.g.)	Sound (NC)			
24 x 24	10	100	HEPA	0.22	-			
		150		0.31	-			
		200		0.41	-			
		250		0.50	-			
		100	ULPA	0.30	-			
		150		0.45	-			
		200		0.61	-			
		250		0.76	-			
24 x 36	10	150	HEPA	0.19	-			
		200		0.24	15			
		250		0.30	19			
		300		0.36	23			
		350		0.42	27			
		400		0.48	30			
		150	ULPA	0.30	-			
		200		0.38	15			
		250		0.45	19			
		300		0.56	23			
		350		0.67	27			
		400		0.75	30			
		24 x 48		12	200	HEPA	0.16	-
					300		0.25	-
400	0.33		-					
500	0.41		17					
600	0.50		23					
200	ULPA		0.27		-			
300			0.39		-			
400			0.50		-			
500			0.63		17			
600			0.74		23			

Performance Notes:

1. sp = Static Pressure, in. w.g.
2. cfm = Air flow in cubic feet per minute, cfm.
3. NC = Noise Criteria. NC values are based on room absorption of 10dB re 10-12 watts.
4. Blanks "-" indicate an NC level below 15.
5. sp and NC at full open damper position.
6. Tested in accordance with ASHRAE Standard 70-2006.